TECHNICAL DATA SHEET



ALUMINUM PAINT

112078

Last Update: January 2012

General Description:

Product based on oil hydrocarbonics resins and aluminum pigmented. It provides a good coating, smooth finish, good hiding power and good resistance to bad weather.

Typical Uses:

Product indicated on the finishing of ferrous substrates used in the metalworking industry and in construction.

Product Specifications:

Color- Silver and Golden Appearance – Glossy Viscosity- (50 - 70)"cF4 Drying: Dust-free- 20 Minutes Dry- 2 Hours Full cure- 6 Hours

VOC (Volatile Organic Compounds): EU limit value for this product (cat.A/i): 600 g/Lt (2007) / 500 g/Lt (2010).

This product contains a maximum of 440.30 g/Lt.*

(Product value ready to be applied. We are not responsible for changes made outside our facilities).

Thinning/ Cleanup:

Dilute 5% - 10% with synthetic thinner

Product Application:

Surfaces must be dry and free from dust, grease and rust. Apply it with paint brush, roller or paint spray gun. After the product application, wash the working material with cellulose thinner.

Coverage Rates:

It is considered as average value 8 to 9 m²/Lt/Coat.

Storage:

Two years in original packages, full and well closed Keep in a dry, well-ventilated place, away from heat and ignition sources and protected from frost and direct sunlight.

Safety Information:

Flammable product.

Harmful product by inhalation and skin contact.

Note: All the information in this technical sheet has been carefully selected and arranged by us. It is based upon our best knowledge on the subject at the date of issuance and is provided in good faith. The information should not be considered as a guarantee of specific properties, but as a description of the products from the point of view of indication and application. It is up to the user to check the information with regard to up-to-dateness and suitability for his intended purpose.

Mod_DP_07.R3

Uncontrolled Copy





^{*} For the silver color