

TECHNICAL DATA SHEET

ANTI-GRAPE MASH PAINT

112081

Last Update: June 2013

General Description:

Product based on acrylic resins in combination with chlorinated rubber.
It presents good adhesion and flexibility.
It has good chemical and mechanical resistance characteristics on concrete, iron and also on wood.

Typical Uses:

Product normally used for paint of grapes containers such as: containers, tanks in plastering and wicker baskets.
It should be noted that a container should only be used after a minimum period of 8 days after painting.

Product Specifications:

Color- Oxide red

Appearance- Glossy

Viscosity- (100 – 120)^ocF4

Drying- Superficial – 1 Hour

Between Coats – 2 Hours

Full Cure- 24 Hours

VOC (Volatile Organic Compounds): EU limit value for this product (cat.A/i): 600 g/Lt (2007) / 500 g/Lt (2010).
This product contains a maximum of 500.00 g/Lt.

(Product value ready to be applied. We are not responsible for changes made outside our facilities).

Thinning/ Cleanup:

Dilution - Exclusively with the appropriate thinner

1st Coat – 5 to 10%

2nd Coat – up to 5%

Cleaning thinner – Cellulose thinner

Product Application:

Surfaces must be dry and free from dust and grease.

In case of repainting, make sure the old paint is well bonded, sanding lightly, clean and degrease very well, before painting.

After appropriate preparation of the surface, apply 2 to 3 coats of paint.

Apply it with paint brush, roller or paint spray gun.

Do not apply the product in very moist or cold environmental conditions; it may cause delays in drying and consequent shelling. Do not dilute the paint too much, it may cause decreased in its resistance.

Coverage Rates:

It is considered as average value 8 to 10 m²/Lt/Coat.

Storage:

Three years in original packages, full and well closed.

Keep in a dry, well-ventilated place, away from heat and ignition sources and protected from frost and direct sunlight.

Safety Information:

Flammable product.

Harmful product by inhalation and skin contact.

Avoid skin and eyes contact.

Use only in well-ventilated areas and away from heat and ignition sources.

Note: All the information in this technical sheet has been carefully selected and arranged by us. It is based upon our best knowledge on the subject at the date of issuance and is provided in good faith. The information should not be considered as a guarantee of specific properties, but as a description of the products from the point of view of indication and application. It is up to the user to check the information with regard to up-to-dateness and suitability for his intended purpose.

Mod_DP_07.R3

Uncontrolled Copy