

CHASSIS BLACK PAINT**112083**

Last Update: January 2012

General Description:

Product based on special synthetic resins, dissolved in aromatic solvents.
It presents good adhesion and good resistance to humidity and heat (80-100° C).

Typical Uses:

Product usually used in the chassis paint, in order to avoid the appearance of corrosion.

Product Specifications:

Color – Black
Appearance – Gloss
Viscosity- 150 – 180 “cF4
Drying - Handle – 1 Hour
Full Cure - 6 Hours

Thinning/ Cleanup:

Thinning and Cleanup – Cellulose thinner

Product Application:

Surfaces must be dry, clean and free from grease.
After appropriate surface preparation, apply two to three coats of paint.
Apply it with paint brush or paint spray gun.

Coverage Rates:

Variable, depending on the application process, can however be regarded as average value 8 to 10 m²/Lt/Coat.

Storage:

Five years in original packages, full and well closed.
Keep in a dry and ventilated place, away from heat and ignition sources and protected from frost and direct sunlight.

Safety Information:

Flammable product
Harmful by inhalation and skin contact
Avoid skin and eyes contact
Use only in well-ventilated areas and away from heat and ignition sources

NOTE: According to the Directive 2004/42/CE, This product can only be used, without restrictions, by professionals and in registered or authorized facilities.

Note: All the information in this technical sheet has been carefully selected and arranged by us. It is based upon our best knowledge on the subject at the date of issuance and is provided in good faith. The information should not be considered as a guarantee of specific properties, but as a description of the products from the point of view of indication and application. It is up to the user to check the information with regard to up-to-dateness and suitability for his intended purpose.