

HIGH TEMPERATURE BLACK PAINT

112082

Last Update: January 2012

General Description:

Product based on special alkyd resins, resistant to heat, dissolved in aromatic solvents. Presents good adhesion and good resistance to humidity and heat (80-100° C).

Typycal Uses:

Product normally used to paint radiators, hot air pipes, chimneys, etc.

Product Specifications:

Color- Black Appearance – Gloss Viscosity - 150 – 180 "cF4 Drying- Dust-free - 30 Minutes Handle – 4 Hours Full cure- 6 Hours

Thinning/ Cleanup:

Thinning and cleaning - Cellulose thinner.

Product Application:

Surfaces must be dry, clean and free from grease. After appropriate surface preparation, apply two to three coats of paint. Apply with paint brush, roller or paint spray gun.

Coverage Rates:

Variable, depending on the application process, can however be regarded as average value 8 to 10 m²/Lt/Coat.

Storage:

Five years in original packages, full and well closed.

Keep in cool and dry place, away from heat and ignition sources and protected from frost and direct sunlight.

Safety Information:

Flammable product.

Harmful product by inhalation and skin contact.

Avoid skin and eyes contact.

Use only in well-ventilated areas and away from heat and ignition sources.

NOTE: According to the Directive 2004/42/CE, this product can only be used, without restrictions, by professionals and in registered or authorized facilities.

Note: All the information in this technical sheet has been carefully selected and arranged by us. It is based upon our best knowledge on the subject at the date of issuance and is provided in good faith. The information should not be considered as a guarantee of specific properties, but as a description of the products from the point of view of indication and application. It is up to the user to check the information with regard to up-to-dateness and suitability for his intended purpose.

Mod_DP_07.R3

Uncontrolled Copy



