

REVESTMENT CERAMIC TILES PAINT

112085

Last Update: January 2007

General Description:

Product based on styrene/acrylic resin with elastic and self-hardenable properties, which forms a homogenous layer, strongly adhering to glazed surfaces, keeping a permanent elasticity.

Typical Uses:

Product indicated for painting revestment ceramic tiles and glazed surfaces, when the point is cover up the aged appearance of old revestment ceramic tiles, or waterproofing the surface to be painted.

Product Specifications:

Color - White and catalogue colors. Appearance - Slightly satin finish Viscosity - (80-85)KU

VOC (Volatile Organic Compounds): EU limit value for this product (cat.A/b): 150 g/Lt (2007) / 100g/Lt (2010). This product contains a maximum of 100.00 g/Lt.* (Product value ready to be applied. We are not responsible for changes made outside our facilities).

Thinning/ Cleanup:

Dilute exclusively with water.

Product Application:

Surfaces must be dry and free from dust and grease.

Apply it with paint brush or roller.

It should be applied in 2 or 3 layers, in order to leave a homogeneous layer, on a sticky primary, previously applied. The first coat should be fairly dilute (± 25%) in order to facilitate adherence to the primary.

Coverage Rates:

It is considered as average value 6 to 8 m²/Lt.

Storage:

Three years in original packages, full and well closed. Keep in a dry, well-ventilated place, protected from heat.

Safety Information:

Not flammable and not harmful product. Keep locked up and away from children.

* For white color

Note: All the information in this technical sheet has been carefully selected and arranged by us. It is based upon our best knowledge on the subject at the date of issuance and is provided in good faith. The information should not be considered as a guarantee of specific properties, but as a description of the products from the point of view of indication and application. It is up to the user to check the information with regard to up-to-dateness and suitability for his intended purpose

Mod_DP_07.R3



