

VERNICRIL (Aqueous Acrylic Varnish)**109366**

Last Update: April 2013

General Description:

Varnish based on pure acrylic aqueous dispersions, with good toughness, good resistance to water, good luster and good flexibility. Formulated for interior and exterior wood varnishing, with a quick drying, absence of solvent odors and easy to apply.

Typical Uses:

Product indicated in the varnishing of doors, frames of doors, windows, baseboards, cabinets in wood, etc. It provides effective protection in Interior and exterior woods, without changing the original tone.

Product Specifications:

Color – Colorless

Appearance – Glossy, Satin and Matte

Viscosity - (70 - 80) "cF4

Drying – (In temperature conditions superior to 10°C and humidity less than 60%)

Superficial (Touch): 30 min. to 1 hour

Re-coating time: Approximately 3 to 4 hours

VOC (Volatile Organic Compounds): EU limit value for this product (cat.A/e): 130 g/Lt (2010)).

This product contains a maximum of 60 g/Lt.

(Product value ready to be applied. We are not responsible for changes made outside our facilities).

Thinning/ Cleanup:

Dilute with 5% water, in the 1st coat.

Other coats, apply as supplied.

Cleaning thinner – Water

Product Specifications:

Surfaces must be dry, firm and free from dust, grease or other contaminants.

On waxed surfaces, completely remove the wax.

In previously varnished surfaces, previously matting with a fine grain sandpaper.

Mix well the product before any application.

Apply one first coat of varnish, thinned up to 5% with water and the remaining coats without dilution, taking care of matting slightly between coats, for a better finish.

Apply the varnish with paint brush, roller, or pain spray gun.

Could be applied as 1st coat our product VOUGADEX, colorless or catalogue colors, if the aim is the change of the original wood color.

Do not apply the product with wet or rainy weather, neither with temperatures above 10°C.

After the product application, wash the working material with water.

Coverage Rates:It is considered as average value 10 to 12 m²/Lt/Coat.**Storage:**

Two years in original packages, full and well closed.

Keep in a dry and ventilated place, protected from frost and direct sunlight.

Safety Information:

It is not a flammable product.

Note: All the information in this technical sheet has been carefully selected and arranged by us. It is based upon our best knowledge on the subject at the date of issuance and is provided in good faith. The information should not be considered as a guarantee of specific properties, but as a description of the products from the point of view of indication and application. It is up to the user to check the information with regard to up-to-dateness and suitability for his intended purpose.